



# MS852B

## Bluetooth® 2D Imager Scanner

Combining mobility wireless design and 2D scanning performance in one scanner, the unitech MS852B wireless scanner delivers the simple way to do the inventory control faster and efficiency for business solutions from warehousing, manufacturing, logistics to general purpose retail scanning. Additionally, it is available to read OCR.

### Move without Restrictions

Featuring 2D scanning technology, the MS852B has the ability to capture most 1D / 2D barcodes on mobile screens, even damaged or poorly printed barcodes. Moreover, the MS852B supports Bluetooth® dual mode technology (Bluetooth® LE V4.2 & Bluetooth® 2.1+EDR, Class 1) to give you the freedom and bring your business the flexibility. It is compatible with any smartphone, tablet, or computer—the MS852B pairs easily to any mobile device or PC. Besides, it allows users to transmit data to the host from up to 100 meters from the base.

### User-Friendly with Cradle Accessory

This MS852B+ wireless scanner has a cradle accessory that supports auto Bluetooth® pairing and it has the ability to switch between trigger or presentation mode automatically. When it is out of range reading in Auto Mode, the scanned data will be saved into the MS852B memory buffer automatically and transmit to the host when back to the wireless coverage. Moreover, MS852B can be set to batch mode reading, all the scanned data will be stored in a memory buffer and upload to your devices at your own convenience.

### Compact but durable

Built for all day use, the MS852B is built in a lithium-ion battery can be replaced easily. It has a long life battery life 20 hours per battery charge. While sustaining a 2.1 meter drop to concrete, MS852B incorporated with IP42 rugged design for protection against dust and moisture. Moreover, the built-in long lifecycle trigger of 10 million times guarantees a continuous productivity for best reliability. This scanner can be used in the most practical way depending on the scanning task in various solutions in retail, warehousing, manufacturing, logistics.

### Features

- Support OCR, most 1D / 2D barcode on mobile screens, even damaged or poorly printed barcodes
- Support Bluetooth® dual mode technology (Bluetooth® LE V4.2 & Bluetooth® 2.1+EDR, Class 1)
- Wireless transmission range up to 100m in the line of open sight
- Long battery life 20 hours per a fully charged battery
- Durable design : IP42 and 2.1m drop spec
- Auto Bluetooth pairing / auto switch between trigger & presentation mode with cradle



# MS852B

## Specifications

### Symbologies

- 1D UPC/EAN/JAN, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5 (ITF), Discrete 2 of 5 (DTF), Codabar (NW - 7), MSI, Chinese 2 of 5, Matrix 2 of 5, Korean 3 of 5, Inverse 1D, GS1 DataBar, Composite Codes
- 2D PDF417, MicroPDF417, Code 128, Data Matrix, GS1 Data Matrix, Data Matrix Inverse, Decode Data Matrix, Maxicode 294, QR Code 293, GS1 QR Code, Micro QR Code, Linked QR Code, Aztec, Aztec Inverse, Han Xin Code, Han Xin Inverse, Grid Matrix, Grid Matrix Inverse, Grid Matrix Mirror, Macro PDF Postal : Australia Post, Australia Post Format, UK Postal, Japan Postal, Netherlands KIX Post, GS1 Composite, Korea Post, US Postnet, US Planet, Transmit US Postal Check Digit Transmit UK Postal Check Digit, USPS 4CB/One Code/Intelligent Mail, UPU FICS Postal, Mailmark

### Electrical

- |                       |  |
|-----------------------|--|
| Indicator             | LED & Beeper & Vibrator                    |
| Battery Type          | Rechargeable and replaceable battery pack. |
| Battery Capacity      | 2850mAh                                    |
| Battery Charging time | <6.5 hours                                 |
| Operating Time        | 20 hours                                   |

### Environmental

- |                       |   |
|-----------------------|---|
| ESD Protection        | Functional after 8K Contact and 15K Air |
| Mechanical Shock      | 2.1M onto concrete (scanner only)       |
| Operating Temperature | -10°C to 50°C (14°F to 122°F)           |
| Storage Temperature   | -40°C to 70°C (-40°F to 158°F)          |
| Relative Humidity     | 95% non-condensing                      |
| IP Rating             | IP42                                    |

### Accessories

- Cradle
- Interface cable
- Battery pack

### Package Contents

- MS852B Scanner with battery
- Cradle
- Interface cable

### Optical & Performance

|                              |   |                 |                   |
|------------------------------|---|-----------------|-------------------|
| Sensor                       | CMOS sensor with 1280 x 960 pixels, rolling shutter |                 |                   |
| Aiming Element               | 610nm, Green LED                                    |                 |                   |
| Illumination                 | 1 warm white LED                                    |                 |                   |
| Skew Angle                   | ± 60°   |                 |                   |
| Pitch Angle Sensor           | ± 60°   |                 |                   |
| Roll Angle                   | 0 - 360°  |                 |                   |
| Optical Resolution           | 5.0 mil (Code 39), 6.6 mil (PDF417)                 |                 |                   |
| Printing Contrast Scale      | Minimum 20%   |                 |                   |
| Depth of Field (DOF PCS=80%) | Barcode type  | Near            | Far               |
|                              | 5 mil Code 39                                       | 2.4 in / 6.1 cm | 9.5 in / 24.1 cm  |
|                              | 5 mil Code 128                                      | 2.8 in / 7.1 cm | 9.0 in / 22.9 cm  |
|                              | 6.67 mil PDF417                                     | 2.4 in / 6.1 cm | 8.0 in / 20.3 cm  |
|                              | 10 mil Data Matrix                                  | 2.9 in / 7.4 cm | 8.5 in / 21.6 cm  |
|                              | 100% UPC  | 1.8 in / 4.6 cm | 19.5 in / 49.5 cm |
|                              | 15 mil QR Code                                      | 1.2 in / 3.0 cm | 11.5 in / 29.2 cm |
|                              | 20 mil QR Code                                      | 1.5 in / 3.8 cm | 11.5 in / 29.2 cm |

### Communication

- |                          |   |
|--------------------------|---|
| Radio                    | Bluetooth® LE V4.2<br>Bluetooth® 2.1+EDR, Class1<br>Dual mode |
| Wireless Coverage        | 100m ( line of sight)   |
| Interface/ Profile       | Serial Port and HID profiles                                  |
| Host Interface supported | USB, RS232  |
| Memory Buffer            | 7MB for batch mode / 20KB for auto mode                       |

### Mechanical

- |                     |                                |
|---------------------|--------------------------------|
| Scanner Dimension   | 87.8 L x 71.6 W x 177.7 H (mm) |
| Scanner Weight      | 213g (without cradle)          |
| Trigger Switch Life | 10 million times               |
| Cradle Dimension    | 120.6 L x 88.7 W x 86.0 H (mm) |

### Regulatory Approvals

CE, FCC, BSMI, VCCI, NCC, TELEC, BQB



#### Headquarters

Taipei, Taiwan  
http://www.ute.com e-mail: info@hq.ute.com

#### unitech America

Los Angeles  
http://us.ute.com e-mail: info@us.ute.com  
http://can.ute.com info@can.ute.com  
Mexico  
http://latin.ute.com e-mail: info@latin.ute.com

#### unitech Asia Pacific & Middle East

Taipei  
http://apac.ute.com info@apac.ute.com / info@india.ute.com  
http://mideast.ute.com info@mideast.ute.com

#### unitech Europe

Tilburg / Netherlands  
http://eu.ute.com e-mail: info@eu.ute.com

#### unitech Japan

Tokyo  
http://jp.ute.com e-mail: info@jp.ute.com

#### unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
http://cn.ute.com info@cn.ute.com  
Taipei http://tw.ute.com info@tw.ute.com



www.ute.com

07/24 Rev.H(SE4107)