

Two-way Radio



DL T-5800

DL T-5800

Professional FM Transceiver

Main Features

- 400-470MHz
- High Battery Capacity
- Tail Elimination
- Power Save
- High/Low Power Switchable
- Monitor
- VOX
- Channel Scanning

| General Specification | | Transmitter | | Receiver | |
|-----------------------------------|------------------------|----------------------------|----------------|------------------------------------|------------|
| Frequency Range | UHF:400-470 mhz | Output Power | 3W | Sensitivity | ≤-122dBm |
| RF Output Power | 3W | Frequency Stability | ±1.5 X 10-6ppm | Adjacent Channel Selectivity | ≥55dB |
| Channels | 16 Channels | Modulation Mode | F3E | Block | ≥84dB |
| Channel Spacing | 25kHz/12.5kHz | Modulation Distortion | ≤-1% | Inter-modulation response immunity | ≥55dB |
| CTCSS/DCS | 50 CTCSS/105 DCS | Modulation Sensitivity | 12±5mV | Rated Output Power | 1000mW@16Ω |
| Antenna Impedence | 50Ω | Transmit Spurious Emission | ≥ 62dB | Rated Audio Distortion | ≤5% |
| Operating Temperature | -30°C+60°C | Adjacent Channel Power | ≥ 65dB | | |
| Working Voltage | DC7.4V | | | | |
| Battery Type | 3800mAh Li-ion Battery | | | | |
| Dimension(excluding antenna) | 126(H)*60(W)*30(D)mm | | | | |
| Weight(Battery, Antenna included) | About 220g | | | | |

(REMARK: The specifications of the product may be modified for improvement without notice)

Standard Accessories



Antenna



Battery



Charger



Belt clip



PROFESSIONAL FM TRANSCEIVER




Monitor



Tail Elimination



VOX



Power Save