



Thermal Receipt Printer
POS80UL USB + LAN

- New sleek shell design
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind



GPOS POS80UL

Thông số kỹ thuật

Hạng mục	Thông số
Printing Method	Thermal Line
Resolution	8 dots/mm (203 dpi), 576 dots/line
Printing Speed	200mm/s (25% printing density)
Font - Spanish	12×24 points
Font - Chinese	24×24 dots
Interface	USB + Ethernet
Support Functions	Paper Out Alarm, Overheating Protection, Voice Broadcast
Cash Drawer Control	DC24V, 1A, 6-wire RJ-11 Socket
Power Requirements	DC24V±10%, 2A, A-1009-3P power socket
Paper Type	Thermal Paper 79.5 × Φ80mm (MAX)
Paper Thickness	0.06 – 0.08mm
Maximum Outer Diameter	Φ80mm
Paper Width	79.5 ± 0.5mm
Paper Cutting Method	Half Cut
Cutter Life	1,500,000 cuts
Print Head Life	150km
Operating Temp/Humidity	5~50°C / 10~80%
Storage Temp/Humidity	-20~60°C / 10~90%
Dimension	165mm × 120mm × 119mm (L×W×H)

CÔNG TY TNHH CÔNG NGHỆ VINH NGUYỄN

Địa chỉ : RR9 Hồng Lĩnh, Phường Hòa Hưng, TP Hồ Chí Minh (Phường 15, Q10 cũ)
MST: 0315101322 | Hotline : 0901 555547 | 0904 555547 | 0908 555547 | 0786 555547
Email : info@vinhnguyen.vn | Website : www.vinhnguyen.vn

