Professional Fingerprint Access Control System
with New Firmware
Made in Thailand

MITA F09

● Introduction

MITA F09 is a professional fingerprint access control terminal with new fingerprint algorithm. High speed processor and better-quality hardware lead to excellent performance and high stability. It's easy to connect with third party electric lock, door sensor and exit button for door access control application. Wiegand input & output interface make F09 enable to utilize Master & Slave solutions, verification at both entrance and exit is avaiable, Meanwhile, anti-passback function could be used to maximize the security level. It supports both standalone and network, comes with free software for management. It's much suitable to install in office, hospital, bank, school and many other places.

● Distinctive Feature

| Photo-ID	Barcode	Data encryption	Webserver	Alarm	Door bell	Anti-passback

● Basic Function

- Latest fingerprint algorithm with friendly user interface
- Support TCP/IP, RS232/485, USB and wiegand in/output
- Special user-role and fingerprint expired management
- ID card /Mifare card or HID card can be customized

- Up to 66 user-defined schedule bell
- Connect with slave reader easily
- Easy to connect with Barcode

Working Application

Standalone

Exit button RFID reader Electric lock Inside Outside MITA F09 Flash disk PC Reports

Network

Ethernet Switch TCP/IP TCP/IP MITA F09 TCP/IP MITA F09 Networked PC with software PC RS485 MITA F09 RS232 RS485 MITA F09 RS232/RS485 Converter

Specification

|	
LCD Display	**Language**
2.4" TFT LCD color screen	Multi language, English, French, Spanish, Arabic, Turkish,
Speaker	Portuguese, Czech, Hebrew, Slavic, Vietnamese etc.,
Voice prompt (language can be selected) Capacity	for more than 40 languages can be selected
Capacity	**Power Supply**
Fingerprint: 4,000	110/220 VAC-12VDC(PS-3A is optional item)
Logs: 100,000	**Package info.**
Verification	Machine size: 19(L)*7.8(W)*4(H)cm
Verification speed (1:1) ≤ 0.5s	Unit packing: 25*15*9cm
Identification speed (1:1) ≤ 1s	Carton packing: 53*33*45cm
Identification	Real weight: 0.95kg
FRR ≤ 0.01% FAR ≤ 0.0001%	Volum weight: 1.0kg
Attendance status	**Function support**
Check in/out, Break in/out, Overtime in/out	Built-in relay, 50 time zones, 5 groups, 10 combinations, alarm,
Communications	door senor, door lock, DST, workcode, webserver, photo-ID,
TCP/IP, RS232/485, USB Host, wiegand in/out	schedule bell, SMS, auto-status, Anti-passback, T9, 9 PIN user ID,
Environment	Log query, external siren, barcode,
Operation temperature: 0°C-45°C	**Customize Function**
Operation humidity: 20%-80%	ID /Mifare/ HID card reader, print function, Multi-verify, ADMS

Packing list


Fingerprint Device   Back Plate   Silica gel pad   Screws   Connection cable   Screw-driver